

PVC INSULATED FLEXIBLE CORDS




EUROPE

H05V-K、H05V2-K



PVC Insulated Single Cords
 Rating:300/500V 70 °C/90 °C
 Standard:DIN VDE 0281-3 HD21.3




| Normal area (mm ²) | Conductor Construction (No./mm) | Insulation thickness (mm) | Overall diameter (mm) | Max Conductor resistance at 20°C | |
|-----------------------------------|---------------------------------------|---------------------------------|-----------------------------|----------------------------------|--------|
| | | | | Ω /km | |
| | | | | Bare | Tinned |
| 0.50 | 0.6 | 16/0.20 | 2.20±0.1 | 39.00 | 40.1 |
| 0.75 | 0.6 | 24/0.20 | 2.40±0.1 | 26.00 | 26.7 |
| 1.00 | 0.6 | 32/0.20 | 2.55±0.1 | 19.50 | 20.0 |

H07V-K、H07V2-K



PVC Insulated Single Cords
 Rating:450/750V 70 °C
 Standard:DIN VDE 0281-3 HD21.3



| Normal area (mm ²) | Conductor Construction (No./mm) | Insulation thickness (mm) | Overall diameter (mm) | Max Conductor resistance at 20°C | |
|-----------------------------------|---------------------------------------|---------------------------------|-----------------------------|----------------------------------|--------|
| | | | | Ω /km | |
| | | | | Bare | Tinned |
| 1.50 | 30/0.25 | 0.7 | 3.15±0.1 | 13.30 | 13.7 |
| 2.50 | 49/0.25 | 0.8 | 3.70±0.1 | 7.98 | 8.21 |
| 4.00 | 56/0.30 | 0.8 | 4.50±0.1 | 4.95 | 5.09 |
| 6.00 | 84/0.30 | 0.8 | 5.40±0.1 | 3.30 | 3.39 |